

Belts

BRICQ-TECH

Very high performance needled belt, specially adapted to high speed machines and very sensitive boards. Its high permeability, increased porosity and special edges give exceptional combination of belt life and quality.



Technical Data

Polyester needled belt

- Weight: 4 200 g/m²
- Thickness: 9.20 mm
Perfect homogenous thickness
- Permeability: 750 m³/m²/h under 300 mm WG.
High permeability and porosity for optimum evaporation
- Porosity: 75 % board side
- Heat setting: High stability
- Guiding control at the end of the manufacturing process :
Provides optimum belt tracking on the machine
- Reinforced base: Additional 66 % traction resistance compared to an ordinary base.

BRICQ S.A.S.
D 62 Route d'Orgedeuil
16220 Montbron, France
Tel. +33 5 45 23 91 11
Fax +33 5 45 70 86 26

info@bricq.fr

Treatment and seam

- Treatment on board side :
Improves belt grip on board side and provides positive board drive
- Treated edges on board side :
New improved treatment, with high resistance to abrasion and non sticking properties (glue) types G/G2
- Integrated seam :
Eliminates clip marks on the board

Options to improve belt performance

- Diagonal seam:
Reduces roll bounce for less noise, less marking and less maintenance costs.
- Treatment on machine side:
Low coefficient of friction